


SMOOTH AND MATTE PU MATERIAL THAT PROVIDES OPTIMAL OPACITY

There is no back-adhesive carrier which makes it perfect for large designs, numbers and letters as the film is so easy to weed. Low cost - very easy to process (no need for capitalizing).



OEKO-TEX® STANDARD 100 17.0.23005 HOHENSTEIN HTTI Geprüft auf Schadstoffe, www.oeko-tex.com/standard100

AVAILABLE IN

50 cm x 25 m rolls

RECOMMENDED FABRICS

- 100% cotton
- 100% polyester*
- Polyester-cotton blends

CUTTING NOTES

You should always test cut prior to any production run. Remember cutter settings will need to be adjusted as the blade ages. For optimal cutting and weeding, maintain a line thickness of at least

1.5 mm for lettering and logos. APPLICATION INSTRUCTIONS

Temperature: 160° C Time: 10 sec. Pressure: medium

(#4-6 on Hotronix®)

Peel: Cold

MULTI-COLOR DESIGNS

Apply background for 3-5 seconds, peel carrier cold. Repeat for additional colors. Finish with final application of 18-20 seconds. Peel cold

ACCESSORIES RECOMMENDED

- Grip Cover Sheet
- Cover Sheet Non-Sticky
- EZ Weeder®

CARE INSTRUCTIONS


Machine wash up to 60° C using mild detergent. Do not use bleach. Dry at normal dryer settings on household machines. Do not dry clean. Iron inside out only.

STORAGE

Store in cool, dry area. Avoid direct heat, sunlight and humidity.

DETAILS







CAD-CUT® BASIC FILM

