
# CAD-COLOR® SUPERTEK™ CLEAR MATT & GLOSS 2.0

# A THIN AND LIGHTWEIGHT POLYURETHANE MATERIAL WITH STIX<sup>2™</sup> ADHESIVE.

Soft touch polyurethane with a great stretch and rebound performance. Ideal for use with lighter white colored performance fabrics. Application at low heat avoids heat press marks or yellowing of garments. Single step application – MagicMask is not necessary. Available in either gloss or matte finish.



50

(++) 🔚 🔯 (150°C 05 sec

#### AVAILABLE IN

Gloss: 50 cm x 22,8 m rolls; Matt: 50 cm x 25 m rolls

#### RECOMMENDED FABRICS

- 100% cotton
- 100% polyester\*
- Polyester-cotton blends
- Lycra<sup>®</sup> / spandex blends
- Most nylon garments\*
- \* Test before application!

## CUTTING NOTES

You should always test cut prior to any production run. Remember cutter settings will need to be adjusted as your blade ages. Cutting too deep will result in weeding or printing difficulties.

#### APPLICATION INSTRUCTIONS

- Temperature: 150° C
- Time: 5 sec.
- Pressure: medium
- (#4-6 on Hotronix<sup>®</sup>)
- Peel: warm

#### ACCESSORIES RECOMMENDED

- Grip Cover Sheet
- Coversheet Non-Sticky
- EZ Weeder<sup>®</sup>

### CARE INSTRUCTIONS

Machine wash up to  $40^\circ$  C using mild detergent. Do not use bleach. Do not dry clean. Can be directly ironed.

#### STORAGE

Store in cool, dry area. Avoid direct heat, sunlight and humidity.

#### DETAILS







